

P/N AB1503D5HW

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AB1503D5HW

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-160-1513

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AB1503D5HW Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.376 Inches Minimum And 0.451 Inches Maximum
Fastener Length:	0.641 Inches Minimum And 0.686 Inches Maximum
Head Style:	Undercut Hexagon
Head Height:	0.155 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.235 Inches Minimum And 0.265 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Special Features:	Furnished With O Ring And Washer
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Astm A304 Assn Std Single Material Response Overall Or Astm A322 Assn Std Single Material Response Overall Or Astm A331 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AB1503D5HW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.