

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AB32A
Minimum Qty (MOQ):	250 EA
NSN:	5320-00-999-0397
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AB3-2A Specifications

Fastener Length:	0.202 Inches Minimum And 0.232 Inches Maximum
Head Style:	Universal
Head Height:	0.022 Inches Minimum And 0.032 Inches Maximum
Shank Diameter:	0.093 Nominal Mils And 0.097 Nominal Centimeters
Shank Style:	Self-plugging
Head Major Diameter:	0.178 Nominal Mils And 0.198 Nominal Centimeters
Expansion Device:	Mandrel-type C
End Item Identification:	Mrap-caiman
Grip Length:	0.040 Nominal Mils And 0.125 Nominal Centimeters
Material:	Aluminum Alloy 5052 Body
Material:	Aluminum Alloy 7178 Mandrel
Material Document And Classification:	Qq-a-200/13 Fed Spec Single Material Response Mandrel
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Surface Treatment:	Anodize Body Or Chromate Body
Surface Treatment:	Anodize Mandrel Or Chromate Mandrel
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-c-5541 Mil Spec 2nd Treatment Response Body
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Mandrel Or Mil-c-5541 Mil Spec 2nd Treatment Response Mandrel

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB3-2A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.