

**Description**

Fastener Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[AD42ABS](#)

SKU / Model:	AB42A
Minimum Qty (MOQ):	100
NSN:	5320-00-510-7823
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AB4-2A Specifications

<b>Fastener Length:</b>	0.222 Inches Minimum And 0.252 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.030 Inches Minimum And 0.040 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Shear Strength:</b>	140 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 5052 Sleeve
<b>Material:</b>	Aluminum Alloy 7178 Stem
<b>Material Document And Classification:</b>	Qq-a-200/13 Fed Spec Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Chromate Sleeve Or Anodize Sleeve
<b>Surface Treatment:</b>	Chromate Stem Or Anodize Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec 1st Treatment Response Stem Or Mil-a-8625 Mil Spec 2nd Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec 1st Treatment Response Sleeve Or Mil-a-8625 Mil Spec 2nd Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB4-2A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.