

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

AD42ABS

| | |
|-------------------------|---------------------|
| SKU / Model: | AB42A |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-510-7823 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N AB4-2A Specifications

| | |
|---|--|
| Fastener Length: | 0.222 Inches Minimum And 0.252 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.030 Inches Minimum And 0.040 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Shear Strength: | 140 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 5052 Sleeve |
| Material: | Aluminum Alloy 7178 Stem |
| Material Document And Classification: | Qq-a-200/13 Fed Spec Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Chromate Sleeve Or Anodize Sleeve |
| Surface Treatment: | Chromate Stem Or Anodize Stem |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Stem Or Mil-a-8625 Mil Spec 2nd Treatment Response Stem |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Sleeve Or Mil-a-8625 Mil Spec 2nd Treatment Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB4-2A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.