

Description

Thread Size: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | AB56 |
| Minimum Qty (MOQ): | 200 EA |
| NSN: | 5320-00-850-3267 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AB5-6 Specifications

| | |
|-------------------------------|---|
| Fastener Length: | 0.504 Inches Nominal |
| Head Style: | Oval/truss |
| Head Height: | 0.039 Inches Nominal |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.312 Inches Nominal |
| Expansion Device: | Knob Stem-type K |
| Fluid Tight Seal Type: | Metal To Metal Contact Head |
| Grip Length: | 0.251 Inches Minimum And 0.375 Inches Maximum |
| Heat Treatment: | As Fabricated Overall |
| Material: | Aluminum Alloy Overall |
| Surface Treatment: | Any Acceptable Overall |

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.