

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AB58
Minimum Qty (MOQ):	500 EA
NSN:	5320-01-079-6817
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N AB5-8 Specifications

Fastener Length:	0.619 Inches Minimum And 0.649 Inches Maximum
Head Style:	Universal
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.376 Inches Minimum And 0.500 Inches Maximum
Material:	Aluminum Alloy 5056 Body
Material:	Steel Comp 1006 Mandrel Or Steel Comp 1008 Mandrel Or Steel Comp 1009 Mandrel Or Steel Comp 1010 Mandrel Or Steel Comp 1011 Mandrel Or Steel Comp 1012 Mandrel Or Steel Comp 1013 Mandrel Or Steel Comp 1015 Mandrel Or Steel Comp 1016 Mandrel Or Steel Comp 1017 Mandrel Or Steel Comp 1018 Mandrel Or Steel Comp 1019 Mandrel Or Steel Comp 1020 Mandrel Or Steel Comp 1021 Mandrel Or Steel Comp 1022 Mandrel Or Steel Comp 1023 Mandrel Or Steel Comp 1524 Mandrel Or Steel Comp 1025 Mandrel
Surface Treatment:	Anodize Body Or Chromate Body
Surface Treatment:	Zinc Mandrel Or Cadmium Mandrel Or Cadmium Mandrel And Chromate Mandrel Or Cadmium Mandrel And Phosphate Mandrel Or Phosphate Mandrel
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-c-5541 Mil Spec 2nd Treatment Response Body

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.