

Description

dome head aluminum rivet - steel mandrel, diameter: 5/32", grip range: 0.251" - 0.375"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | AB56A |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-395-6494 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N AB56A Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.510 Inches Minimum And 0.540 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.039 Inches Minimum And 0.047 Inches Maximum |
| Shank Diameter: | 0.156 Inches Nominal |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.251 Inches Minimum And 0.375 Inches Maximum |
| Material: | Aluminum Alloy 5052 Body |
| Material: | Aluminum Alloy 7178 Mandrel |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB56A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.