

**Description**

Fastener Length: 3/16", Hole Diameter: 1/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AB66
Minimum Qty (MOQ):	170 EA
NSN:	5320-00-938-6234
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AB6-6 Specifications

<b>Fastener Length:</b>	0.188 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Hole Diameter:</b>	0.062 Inches Minimum And 0.066 Inches Maximum
<b>Shank Diameter:</b>	0.085 Inches Minimum And 0.089 Inches Maximum
<b>Shank Style:</b>	Tubular
<b>Head Major Diameter:</b>	0.166 Inches Minimum And 0.176 Inches Maximum
<b>Hole Depth:</b>	0.057 Inches Minimum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Copper Alloy Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.