

Description

Fastener Length: 3/16", Hole Diameter: 1/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AB66
Minimum Qty (MOQ):	170 EA
NSN:	5320-00-938-6234
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N AB6-6 Specifications

Fastener Length:	0.188 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Hole Diameter:	0.062 Inches Minimum And 0.066 Inches Maximum
Shank Diameter:	0.085 Inches Minimum And 0.089 Inches Maximum
Shank Style:	Tubular
Head Major Diameter:	0.166 Inches Minimum And 0.176 Inches Maximum
Hole Depth:	0.057 Inches Minimum
Countersink Angle:	100.0 Degrees Nominal
Material:	Copper Alloy Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.