

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AB68
Minimum Qty (MOQ):	200 EA
NSN:	5320-00-850-3264
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N AB6-8 Specifications

Fastener Length:	0.652 Inches Nominal
Head Style:	Oval/truss
Head Height:	0.047 Inches Nominal
Shank Diameter:	0.187 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.375 Inches Nominal
Expansion Device:	Knob Stem-type K
Grip Length:	0.376 Inches Minimum And 0.500 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Aluminum Alloy 5056 Stem
Material Document And Classification:	Astm B316 Assn Std 1st Material Response Sleeve
Material Document And Classification:	Astm B316 Assn Std 1st Material Response Stem
Surface Treatment:	Anodize Sleeve
Surface Treatment:	Anodize Stem

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.