

Description

dome head aluminum rivet - aluminum mandrel diameter: 3/16", grip range: 0.376" - 0.500"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AB68A |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-408-9928 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N AB6-8A Specifications

| | |
|---|--|
| Fastener Length: | 0.642 Inches Minimum And 0.672 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.045 Inches Minimum And 0.055 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.376 Inches Minimum And 0.500 Inches Maximum |
| Material: | Aluminum Alloy 5052 Body |
| Material: | Aluminum Alloy 7178 Mandrel |
| Material Document And Classification: | Qq-a-200/13 Fed Spec Single Material Response Mandrel |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Body |
| Surface Treatment: | Chromate Body Or Anodize Body |
| Surface Treatment: | Chromate Mandrel Or Anodize Mandrel |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Body Or Mil-a-8625 Mil Spec 2nd Treatment Response Body |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Mandrel Or Mil-a-8625 Mil Spec 2nd Treatment Response Mandrel |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB6-8A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.