

Description

Fastener Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AB86
Minimum Qty (MOQ):	115 EA
NSN:	5320-00-850-3256
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N AB8-6 Specifications

Fastener Length:	0.572 Inches Nominal
Head Style:	Oval/truss
Head Height:	0.069 Inches Nominal
Shank Diameter:	0.250 Inches Nominal
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.500 Inches Nominal
Expansion Device:	Plain Stem-type T
Grip Length:	0.251 Inches Minimum And 0.375 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Aluminum Alloy 5056 Stem
Material Document And Classification:	Astm B316 Assn Std 1st Material Response Sleeve
Material Document And Classification:	Astm B316 Assn Std 1st Material Response Stem
Surface Treatment:	Anodize Sleeve
Surface Treatment:	Cadmium Stem

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AB8-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.