

Description

dome head, open end, aluminum rivet, steel mandrel diameter: 3/32", grip range: 0.032" - 0.125

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AB3-2A](#)

SKU / Model:	AD32BS
Minimum Qty (MOQ):	100
NSN:	5320-00-860-6605
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AD32BS Specifications

Fastener Length:	0.217 Inches Nominal
Head Style:	Universal
Head Height:	0.022 Inches Minimum And 0.032 Inches Maximum
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.178 Inches Minimum And 0.198 Inches Maximum
Expansion Device:	Knob Stem-type K
Grip Length:	0.040 Inches Minimum And 0.125 Inches Maximum
Material:	Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430,o Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Film Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD32BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.