

Description

dome head, open end, aluminum rivet, aluminum mandrel, diameter: 1/8", grip range: 0.063" - 0.125

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AB4-2A](#)

SKU / Model:	AD42ABS
Minimum Qty (MOQ):	100
NSN:	5320-00-510-7823
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AD42ABS Specifications

Fastener Length:	0.222 Inches Minimum And 0.252 Inches Maximum
Head Style:	Universal
Head Height:	0.030 Inches Minimum And 0.040 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	140 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5052 Sleeve
Material:	Aluminum Alloy 7178 Stem
Material Document And Classification:	Qq-a-200/13 Fed Spec Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve Or Anodize Sleeve
Surface Treatment:	Chromate Stem Or Anodize Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Stem Or Mil-a-8625 Mil Spec 2nd Treatment Response Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Sleeve Or Mil-a-8625 Mil Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD42ABS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.