

**Description**

Fastener Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AD43AH
Minimum Qty (MOQ):	100
NSN:	5320-00-343-5435
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N AD43AH Specifications

<b>Fastener Length:</b>	0.342 Inches Minimum And 0.372 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.031 Inches Minimum And 0.051 Inches Maximum
<b>Shank Diameter:</b>	0.120 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.224 Inches Minimum And 0.248 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Shear Strength:</b>	95 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD43AH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.