

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AD43AH
Minimum Qty (MOQ):	100
NSN:	5320-00-343-5435
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AD43AH Specifications

Fastener Length:	0.342 Inches Minimum And 0.372 Inches Maximum
Head Style:	Universal
Head Height:	0.031 Inches Minimum And 0.051 Inches Maximum
Shank Diameter:	0.120 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.224 Inches Minimum And 0.248 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Shear Strength:	95 Single Pounds Per Square Inch
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD43AH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.