

P/N AD44H

Military-Fasteners.com

Description

Fastener Length: 3/8",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AD44H
Minimum Qty (MOQ):	25
NSN:	5320-00-882-8386
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N AD44H Specifications

Fastener Length:	0.373 Inches Minimum And 0.403 Inches Maximum
Head Style:	Universal
Head Height:	0.026 Inches Minimum And 0.046 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.224 Inches Minimum And 0.248 Inches Maximum
Expansion Device:	Plain Stem-type T
End Item Identification:	W/s: Aircraft, Prowler Ea-6b; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Engine, T700-ge-701c (ah-64); Engine, T700-ge-701 (uh-60 & Eh-60a); Trainer, B-1b Aircraft; Aircraft, C-2a (reprocured); Tactical Air Opns Module (an/tyq-23); Engine, Aircraft, F110-ge-100/129 (f-16c/d); Helicopter, Mh-53e; Communications Terminal, Satellite An/gsc-39(v)1
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Aluminum Alloy 5056 Body
Material:	Steel Mandrel
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Surface Treatment:	Zinc Mandrel And Chromate Mandrel
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Body And Mil-c-5541 Mil Spec 2nd Treatment Response Body
Surface Treatment Document And Classification:	Qq-z-325 Ty 2 Cl 3 Fed Spec Single Treatment Response Mandrel

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/AD44H</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.