

**Description**

dome head - open end - aluminum rivet - steel mandrel, diameter: 5/32", grip range: 0.063" - 0.125"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AD52BS                                      |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-067-7082                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N AD52BS Specifications

|                             |   |
|-----------------------------|---|
| <b>Fastener Length:</b>     | 0.244 Inches Minimum And 0.274 Inches Maximum |
| <b>Head Style:</b>          | Universal                                     |
| <b>Head Height:</b>         | 0.037 Inches Minimum And 0.047 Inches Maximum |
| <b>Shank Diameter:</b>      | 0.155 Inches Minimum And 0.159 Inches Maximum |
| <b>Head Major Diameter:</b> | 0.296 Inches Minimum And 0.328 Inches Maximum |
| <b>Expansion Device:</b>    | Plain Stem-type T                             |
| <b>Grip Length:</b>         | 0.040 Inches Minimum And 0.125 Inches Maximum |
| <b>Material:</b>            | Aluminum Alloy 5056 Overall                   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD52BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.