

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AD52H
Minimum Qty (MOQ):	100
NSN:	5320-00-462-2320
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AD52H Specifications

Fastener Length:	0.300 Inches Minimum And 0.320 Inches Maximum
Head Style:	Oval/truss
Head Height:	0.040 Inches Minimum And 0.060 Inches Maximum
Shank Diameter:	0.154 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.305 Inches Minimum And 0.319 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.025 Inches Minimum And 0.125 Inches Maximum
Material:	Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430,o Fed Spec Single Material Response Overall
Surface Treatment:	Any Acceptable Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD52H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.