

**Description**

diameter: 5/32", grip range: 0.188" - 0.25", dome head, open end, aluminum mandrel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AD54ABS
Minimum Qty (MOQ):	100
NSN:	5320-00-938-6713
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N AD54ABS Specifications

<b>Fastener Length:</b>	0.369 Inches Minimum And 0.399 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.037 Inches Minimum And 0.047 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	225 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 5052 Body
<b>Material:</b>	Aluminum Alloy 7178 Mandrel
<b>Material Document And Classification:</b>	Qq-a-200/13 Fed Spec Single Material Response Mandrel
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Body
<b>Surface Treatment:</b>	Anodize Body Or Chromate Body
<b>Surface Treatment:</b>	Anodize Mandrel Or Chromate Mandrel
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-c-5541 Mil Spec 2nd Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Mandrel Or Mil-c-5541 Mil Spec 2nd Treatment Response Mandrel

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD54ABS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.