

Description

Fastener Length: 3/8", dome

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AD64ABS
Minimum Qty (MOQ):	100
NSN:	5320-00-493-4101
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N AD64ABS Specifications

Fastener Length:	0.392 Inches Minimum And 0.422 Inches Maximum
Head Style:	Universal
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	295 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5052 Body
Material:	Aluminum Alloy 7178 Stem
Material Document And Classification:	Qq-430 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-a-200/13 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Body
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD64ABS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.