

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | AD64H |
| Minimum Qty (MOQ): | 200 EA |
| NSN: | 5320-00-956-7355 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N AD64H Specifications

| | |
|---------------------------------|--|
| Fastener Length: | 0.450 Inches Nominal |
| Head Style: | Oval/truss |
| Head Height: | 0.066 Inches Nominal |
| Shank Diameter: | 0.188 Inches Nominal |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.375 Inches Nominal |
| Expansion Device: | Knob Stem-type K |
| End Item Identification: | W/s:submarine Auxillary And Miscellaneous Systems; Support Equipment, B-1 Aircraft; Missile, Air Intercept, Sidewinder (aim-9); Trident Hull Structure; Helicopter, Mh-53e; Helicopter, Advance Attack, Ah-1w; Aircraft, C-2a (reprocured); Shop Equipment, Contact Maintenance, Truck Mounted; Shop Equipment, Electrical Repair, Trailer, Semi-mounted; Central Office, Telephone Auto |
| Grip Length: | 0.126 Inches Minimum And 0.250 Inches Maximum |
| Material: | Aluminum Alloy Overall |

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD64H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.