

**Description**

diameter: 3/16", grip range: 0.251" - 0.375", dome head, aluminum mandrel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AB6-6A](#)

SKU / Model:	AD66ABS
Minimum Qty (MOQ):	100
NSN:	5320-00-409-6841
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N AD66ABS Specifications

<b>Fastener Length:</b>	0.517 Inches Minimum And 0.547 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.251 Inches Minimum And 0.375 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5052 Body
<b>Material:</b>	Aluminum Alloy 7178 Mandrel
<b>Material Document And Classification:</b>	Qq-a-200/13 Fed Spec Single Material Response Mandrel
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Body
<b>Surface Treatment:</b>	Chromate Body Or Anodize Body
<b>Surface Treatment:</b>	Chromate Mandrel Or Anodize Mandrel
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec 1st Treatment Response Body Or Mil-a-8625 Mil Spec 2nd Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec 1st Treatment Response Mandrel Or Mil-a-8625 Mil Spec 2nd Treatment Response Mandrel

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD66ABS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.