

Description

diameter: 3/16", grip range: 0.251" - 0.375", dome head, aluminum mandrel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AB6-6A](#)

SKU / Model:	AD66ABS
Minimum Qty (MOQ):	100
NSN:	5320-00-409-6841
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AD66ABS Specifications

Fastener Length:	0.517 Inches Minimum And 0.547 Inches Maximum
Head Style:	Universal
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.251 Inches Minimum And 0.375 Inches Maximum
Material:	Aluminum Alloy 5052 Body
Material:	Aluminum Alloy 7178 Mandrel
Material Document And Classification:	Qq-a-200/13 Fed Spec Single Material Response Mandrel
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Surface Treatment:	Chromate Body Or Anodize Body
Surface Treatment:	Chromate Mandrel Or Anodize Mandrel
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Body Or Mil-a-8625 Mil Spec 2nd Treatment Response Body
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Mandrel Or Mil-a-8625 Mil Spec 2nd Treatment Response Mandrel

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD66ABS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.