

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AD66AH
Minimum Qty (MOQ):	85 EA
NSN:	5320-00-433-9920
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AD66AH Specifications

Fastener Length:	0.565 Inches Minimum And 0.595 Inches Maximum
Head Style:	Universal
Head Height:	0.061 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.181 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.357 Inches Minimum And 0.393 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.251 Inches Minimum And 0.375 Inches Maximum
Material:	Aluminum Alloy 7178 Stem
Material:	Aluminum Alloy 1100 Sleeve

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD66AH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.