

Description

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AD66AH
Minimum Qty (MOQ):	85 EA
NSN:	5320-00-433-9920
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N AD66AH Specifications

<b>Fastener Length:</b>	0.565 Inches Minimum And 0.595 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.061 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.181 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.357 Inches Minimum And 0.393 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.251 Inches Minimum And 0.375 Inches Maximum
<b>Material:</b>	Aluminum Alloy 7178 Stem
<b>Material:</b>	Aluminum Alloy 1100 Sleeve

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD66AH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.