

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AD68ABS
Minimum Qty (MOQ):	145 EA
NSN:	5320-00-408-9928
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N AD68ABS Specifications

Fastener Length:	0.642 Inches Minimum And 0.672 Inches Maximum
Head Style:	Universal
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.376 Inches Minimum And 0.500 Inches Maximum
Material:	Aluminum Alloy 5052 Body
Material:	Aluminum Alloy 7178 Mandrel
Material Document And Classification:	Qq-a-200/13 Fed Spec Single Material Response Mandrel
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Surface Treatment:	Chromate Body Or Anodize Body
Surface Treatment:	Chromate Mandrel Or Anodize Mandrel
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Body Or Mil-a-8625 Mil Spec 2nd Treatment Response Body
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Mandrel Or Mil-a-8625 Mil Spec 2nd Treatment Response Mandrel

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AD68ABS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.