

## P/N AD68BS

### **Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AD68BS
Minimum Qty (MOQ): 200 EA

NSN: 5320-00-850-3264

Schedule B: 7616.10.3000

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AD68BS Specifications**

Fastener Length:	0.652 Inches Nominal
Head Style:	Oval/truss
Head Height:	0.047 Inches Nominal
Shank Diameter:	0.187 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.375 Inches Nominal
Expansion Device:	Knob Stem-type K
Grip Length:	0.376 Inches Minimum And 0.500 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Aluminum Alloy 5056 Stem
Material Document And Classification:	Astm B316 Assn Std 1st Material Response Sleeve
Material Document And Classification:	Astm B316 Assn Std 1st Material Response Stem
Surface Treatment:	Anodize Sleeve
Surface Treatment:	Anodize Stem

# **How to Order**

Order this pop rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/AD68BS">https://military-fasteners.com/rivets/blind+rivets/AD68BS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/AD68BS">https://military-fasteners.com/rivets/blind+rivets/AD68BS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/AD68BS">https://military-fasteners.com/rivets/blind+rivets/AD68BS</a> and selecting the quantity you want then click "add to cart".