

**Description**

diameter: 7/8", lenght: 12", single layer of braided fiberglass tubing impregnated with flame resistant silicone rubber, temperature range: -65 degrees to -500 degrees

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AE10214
Minimum Qty (MOQ):	1 Per Foot
NSN:	5640-01-009-0041
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N AE102-14 Specifications

<b>Layer Quantity:</b>	1
<b>Fabrication Method:</b>	Braided
<b>Flammability Rating:</b>	Incombustible
<b>Outer Covering Environmental Protection:</b>	Fire Retardant
<b>Insulation Thickness:</b>	0.125 Inches Nominal
<b>Inside Diameter:</b>	0.875 Inches Nominal
<b>Length:</b>	48.000 Inches Nominal
<b>Design Form:</b>	Full Round
<b>Temp Rating:</b>	-65.0 Deg Fahrenheit Minimum And 500.0 Deg Fahrenheit Maximum
<b>Special Features:</b>	Surface Treatment;silicone Rubber
<b>Flexibility:</b>	Flexible
<b>Material:</b>	Glass Fiber
<b>Material:</b>	Glass Fiber
<b>Surface Treatment:</b>	Silicone Rubber
<b>Specification/standard Data:</b>	81343-as 1072b-14-sil-fg Professional/industrial Association Standard

## How to Order

Order this thermal insulation sleeve from our inventory online by visiting <https://military-fasteners.com/shop+supplies/thermal+insulation+sleeving/AE102-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.