

Description

diameter: 7/8", lenght: 12", single layer of braided fiberglass tubing impregnated with flame resistant silicone rubber, temperature range: -65 degrees to -500 degrees

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AE10214
Minimum Qty (MOQ):	1 Per Foot
NSN:	5640-01-009-0041
ECCN:	EAR99



* See page 2 for technical characteristics

P/N AE102-14 Specifications

Layer Quantity:	1
Fabrication Method:	Braided
Flammability Rating:	Incombustible
Outer Covering Environmental Protection:	Fire Retardant
Insulation Thickness:	0.125 Inches Nominal
Inside Diameter:	0.875 Inches Nominal
Length:	48.000 Inches Nominal
Design Form:	Full Round
Temp Rating:	-65.0 Deg Fahrenheit Minimum And 500.0 Deg Fahrenheit Maximum
Special Features:	Surface Treatment;silicone Rubber
Flexibility:	Flexible
Material:	Glass Fiber
Material:	Glass Fiber
Surface Treatment:	Silicone Rubber
Specification/standard Data:	81343-as 1072b-14-sil-fg Professional/industrial Association Standard

How to Order

Order this thermal insulation sleeve from our inventory online by visiting <https://military-fasteners.com/shop+supplies/thermal+insulation+sleeving/AE102-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.