

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | AF3522403 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-150-2739 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AF3522-4-03 Specifications

| | |
|--|--|
| Fastener Length: | 0.510 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.126 Inches Nominal |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.225 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Nickel Alloy Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |
| Material Document And Classification: | Ams5657 Assn Std 3rd Material Response Stem |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec 2nd Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AF3522-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.