

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AF3524502
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-164-1677
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N AF3524-5-02 Specifications

<b>Fastener Length:</b>	0.200 Inches Minimum And 0.230 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Minimum And 0.160 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.247 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.065 Inches Minimum And 0.125 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy 400 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AF3524-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.