

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AF3553503
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-041-6453
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N AF3553-5-03 Specifications

Fastener Length:	0.299 Inches Minimum And 0.319 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
End Item Identification:	Wsd: Aircraft, Galaxy C-5; Aircraft, Eagle F-15; Helicopter, Iroquois Hh/uh-1; Aircraft, Thunderbolt Ii, A-10; Aircraft, Freedom Fighter F-5; Aircraft, Hercules C-130; Aircraft, Starlifter C-141; Aircraft, F-111; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Aircraft, Phantom F-4
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material:	Steel Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AF3553-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.