

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AGS2040510
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-923-3908
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N AGS2040-510 Specifications

Fastener Length:	0.312 Inches Nominal
Head Style:	Universal
Head Height:	0.047 Inches Minimum And 0.057 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.245 Inches Minimum And 0.255 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2040-510> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.