

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AGS2050319BS
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-384-4654
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N AGS2050-319BS Specifications

<b>Fastener Length:</b>	0.1850 Inches Minimum And 0.2050 Inches Maximum
<b>Head Style:</b>	Flat (tubular)
<b>Head Height:</b>	0.0170 Inches Minimum And 0.0230 Inches Maximum
<b>Shank Diameter:</b>	0.1084 Inches Minimum And 0.1184 Inches Maximum
<b>Shank Style:</b>	Tubular
<b>Head Major Diameter:</b>	0.1850 Inches Minimum And 0.1990 Inches Maximum
<b>Special Features:</b>	Break Stem
<b>Material:</b>	Nickel Alloy Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-319BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.