

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AGS2050319BS
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-384-4654
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N AGS2050-319BS Specifications

Fastener Length:	0.1850 Inches Minimum And 0.2050 Inches Maximum
Head Style:	Flat (tubular)
Head Height:	0.0170 Inches Minimum And 0.0230 Inches Maximum
Shank Diameter:	0.1084 Inches Minimum And 0.1184 Inches Maximum
Shank Style:	Tubular
Head Major Diameter:	0.1850 Inches Minimum And 0.1990 Inches Maximum
Special Features:	Break Stem
Material:	Nickel Alloy Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-319BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.