

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AGS2050319BS |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5320-01-384-4654 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

P/N AGS2050-319BS Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.1850 Inches Minimum And 0.2050 Inches Maximum |
| Head Style: | Flat (tubular) |
| Head Height: | 0.0170 Inches Minimum And 0.0230 Inches Maximum |
| Shank Diameter: | 0.1084 Inches Minimum And 0.1184 Inches Maximum |
| Shank Style: | Tubular |
| Head Major Diameter: | 0.1850 Inches Minimum And 0.1990 Inches Maximum |
| Special Features: | Break Stem |
| Material: | Nickel Alloy Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-319BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.