

P/N AGS2050-424BH

Military-Fasteners.com

Description

Pop Rivet part number

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	AGS2050424BH
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-185-3395
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N AGS2050-424BH Specifications

Head Style:	Oval/truss
Head Height:	0.022 Inches Minimum And 0.028 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.229 Inches Minimum And 0.243 Inches Maximum
Expansion Device:	Break Head
Grip Length:	0.140 Inches Maximum
Material:	Nickel Alloy Overall
Material Document And Classification:	D.t.d. 10b Fscm K0289 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	D.t.d. 904 Fscm K0289 Mfr Ref Single Treatment Response Overall

How to Order

Order this pop rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/AGS2050-424BH</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.