

Description

Pop Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AGS2050429BS
Minimum Qty (MOQ):	50
NSN:	5320-01-179-0606
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N AGS2050-429BS Specifications

Head Style:	Oval/truss
Head Height:	0.022 Inches Minimum And 0.028 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.229 Inches Minimum And 0.243 Inches Maximum
Expansion Device:	Break Stem
Grip Length:	0.170 Inches Maximum
Material:	Nickel Alloy Overall
Material Document And Classification:	D.t.d. 10b Fscm K0289 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	D.t.d. 904 Fscm K0289 Mfr Ref Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-429BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.