

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AGS2050519BH |
| Minimum Qty (MOQ): | 45 EA |
| NSN: | 5320-01-046-3952 |
| Schedule B: | 7508.90.5000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AGS2050-519BH Specifications

| | |
|---|--|
| Fastener Length: | 0.190 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.025 Inches Minimum And 0.031 Inches Maximum |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Expansion Device: | Mandrel-type C |
| Grip Length: | 0.050 Inches Nominal |
| Material: | Nickel Alloy Mandrel |
| Material: | Nickel Alloy Body |
| Surface Treatment: | Cadmium Body |
| Surface Treatment: | Cadmium Mandrel |
| Surface Treatment Document And Classification: | Dtd 904,fscm K0379 Mfr Ref Single Treatment Response Body |
| Surface Treatment Document And Classification: | Dtd 904,fscm K0379 Mfr Ref Single Treatment Response Mandrel |

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-519BH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.