

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AGS2050519BH
Minimum Qty (MOQ):	45 EA
NSN:	5320-01-046-3952
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N AGS2050-519BH Specifications

Fastener Length:	0.190 Inches Nominal
Head Style:	Universal
Head Height:	0.025 Inches Minimum And 0.031 Inches Maximum
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.050 Inches Nominal
Material:	Nickel Alloy Mandrel
Material:	Nickel Alloy Body
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Mandrel
Surface Treatment Document And Classification:	Dtd 904,fscm K0379 Mfr Ref Single Treatment Response Body
Surface Treatment Document And Classification:	Dtd 904,fscm K0379 Mfr Ref Single Treatment Response Mandrel

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-519BH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.