

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AGS2050524BH
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-467-7103
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AGS2050-524BH Specifications

Fastener Length:	0.235 Inches Minimum And 0.255 Inches Maximum
Head Style:	Universal
Head Height:	0.025 Inches Minimum And 0.031 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Material:	Nickel Alloy Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	D.t.d. 904 Fscm U1653 Mfr Ref Single Treatment Response Overall

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-524BH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.