

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AGS2050524BS
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-150-3824
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AGS2050-524BS Specifications

Fastener Length:	0.235 Inches Minimum And 0.255 Inches Maximum
Head Style:	Universal
Head Height:	0.025 Inches Minimum And 0.031 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Nickel Alloy Stem
Material:	Nickel Alloy Body
Material Document And Classification:	Monel,fscm 05457 Mfr Ref Single Material Response Body
Material Document And Classification:	Monel,fscm 05457 Mfr Ref Single Material Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	D.t.d. 904,fscm 05457 Mfr Ref Single Treatment Response Stem
Surface Treatment Document And Classification:	D.t.d.904,fscm 05457 Mfr Ref Single Treatment Response Body

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-524BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.