

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AGS2050524BS |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-00-150-3824 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N AGS2050-524BS Specifications

| | |
|---|--|
| Fastener Length: | 0.235 Inches Minimum And 0.255 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.025 Inches Minimum And 0.031 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Material: | Nickel Alloy Stem |
| Material: | Nickel Alloy Body |
| Material Document And Classification: | Monel,fscm 05457 Mfr Ref Single Material Response Body |
| Material Document And Classification: | Monel,fscm 05457 Mfr Ref Single Material Response Stem |
| Surface Treatment: | Cadmium Body |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | D.t.d. 904,fscm 05457 Mfr Ref Single Treatment Response Stem |
| Surface Treatment Document And Classification: | D.t.d.904,fscm 05457 Mfr Ref Single Treatment Response Body |

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-524BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.