

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AGS2050524BS
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-150-3824
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AGS2050-524BS Specifications

<b>Fastener Length:</b>	0.235 Inches Minimum And 0.255 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.025 Inches Minimum And 0.031 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Material:</b>	Nickel Alloy Stem
<b>Material:</b>	Nickel Alloy Body
<b>Material Document And Classification:</b>	Monel,fscm 05457 Mfr Ref Single Material Response Body
<b>Material Document And Classification:</b>	Monel,fscm 05457 Mfr Ref Single Material Response Stem
<b>Surface Treatment:</b>	Cadmium Body
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	D.t.d. 904,fscm 05457 Mfr Ref Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	D.t.d.904,fscm 05457 Mfr Ref Single Treatment Response Body

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2050-524BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.