

Description

Pop Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | AGS2051419BH |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5320-01-179-0607 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AGS2051-419BH Specifications

| | |
|---|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.243 Inches Maximum |
| Expansion Device: | Break Head |
| Grip Length: | 0.120 Inches Maximum |
| Countersink Angle: | 120.0 Degrees Minimum And 122.0 Degrees Maximum |
| Material: | Nickel Alloy Overall |
| Material Document And Classification: | D.t.d. 10b Fscm K0289 Mfr Ref Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | D.t.d. 904 Fscm K0289 Mfr Ref Single Treatment Response Overall |

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2051-419BH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.