

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AGS2051524BS
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-162-9762
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AGS2051-524BS Specifications

Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Brazier
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.254 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.600 Inches Minimum And 0.650 Inches Maximum
Heat Treatment:	H-14 Strain Hardened, 1/2 Hard Overall
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2051-524BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.