

**Description**

Pop Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AGS2051537BS
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-179-0605
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AGS2051-537BS Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.270 Inches Maximum
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.260 Inches Maximum
<b>Countersink Angle:</b>	120.0 Degrees Minimum And 122.0 Degrees Maximum
<b>Material:</b>	Nickel Alloy Overall
<b>Material Document And Classification:</b>	D.t.d. 10b Fscm K0289 Mfr Ref Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	D.t.d. 904 Fscm K0289 Mfr Ref Single Treatment Response Overall

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AGS2051-537BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.