

P/N AGS2051-537BS

Military-Fasteners.com

## Description

Pop Rivet part number

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

Order this part online

## **Additional Information**

SKU / Model:	AGS2051537BS
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-179-0605
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



## P/N AGS2051-537BS Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.270 Inches Maximum
Expansion Device:	Break Stem
Grip Length:	0.260 Inches Maximum
Countersink Angle:	120.0 Degrees Minimum And 122.0 Degrees Maximum
Material:	Nickel Alloy Overall
Material Document And Classification:	D.t.d. 10b Fscm K0289 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	D.t.d. 904 Fscm K0289 Mfr Ref Single Treatment Response Overall

## How to Order

Order this pop rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/AGS2051-537BS</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.