

**Description**

Diameter: 1/4", slotted, steel comp

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AJ325                                     |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5325-00-282-8138                          |
| Schedule B:             | 7318.15.5030                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N AJ3-25 Specifications

|   |   |
|---|---|
| <b>Grip Length:</b>                     | 0.240 Inches Minimum And 0.260 Inches Maximum |
| <b>Diameter:</b>                        | 0.312 Inches Nominal                          |
| <b>Turnlock Stud Shank Style:</b>       | Stud Shank                                    |
| <b>Turnlock Stud Head Style:</b>        | Fillister                                     |
| <b>Material Accommodated Thickness:</b> | 0.240 Inches Minimum And 0.260 Inches Maximum |
| <b>Drive Type:</b>                      | Slotted                                       |
| <b>Shank Neck Length:</b>               | 0.065 Inches Minimum And 0.085 Inches Maximum |
| <b>Stud Shank Major Diameter:</b>       | 0.182 Inches Minimum And 0.187 Inches Maximum |
| <b>Material:</b>                        | Steel Comp 1315 Overall                       |
| <b>Surface Treatment:</b>               | Cadmium Overall                               |

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/AJ3-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.